



ELECTRICAL CHARACTERISTICS : (TRUE V.34 FOR SMT)

- DCR PIN 1-3 = 150Ω ± 10% PIN 4-6 = 150Ω ± 10%
- INDUCTANCE (@250Hz, 0.5Vrms, PARALLEL) 1-3 = 4.0H MIN.
- IMPEDANCE (@1KHz, 0dBm, 6-4 W/H 301Ω)
 - 1-3 = 600Ω ± 2%
- INSERTION LOSS = 3.3 ± 0.25dB
 - (@1KHz, 0dBm, W/H 301Ω LOAD)
- FREQ. RESP. (@300Hz TO 4KHz, REF. 1KHz) = ± 0.1dB
- RETURN LOSS @300Hz = 30dB MIN. @1KHz = 35dB MIN.
 - @4KHz, = 35dB MIN.
- TURN RATIO = 1:1 ± 1%
- POLARITY = PIN 1-6 INPHASE
- LONGITUDINAL BAL. = 70dB MIN. (@200Hz TO 4KHz)
- T.H.D (@600Hz, -10dBm) = -82dB MAX.
- HI-POT = 1250 VAC, 1mA, 2SEC. (PRI.-SEC.)
- LEAD-FREE

A	 苏州沃虎电子科技有限公司 Su Zhou Voohu Electronic Tech.Co.Ltd	TITLE: 600:301 TRANSFORMER	SIZE A4	UNITS MM[INCH]	GENERAL TOLERANCES UNLESS SPECIFIED		APPROVED BY: Geoffrey.Song	
		PART NO.: ATS-182BN-R	SACLE 1:1	REV A0	x±0.35	x°±3.0°	CHECKED BY: Elvis.Song	
		REMARK:	SHEET 1/1		.xx±0.25	.xx°±1.5°	DESIGND BY: Sunny.Xu	
	TEL: +86 400 1048 018	WEB: WWW.WOHU-TEK.COM				.xxx±0.10	.xxx°±1.0°	