



ELECTRICAL CHARACTERISTICS:

- ① 1. DCR: PIN3-4=133 OHM MAX at 20°C
PIN1-2=160 OHM MAX
- 2. INDUCTANCE: (@1kHz, 0. 3Vrms)
PIN1-2=3-4=1. 1H MIN
- 3. LEAKAGE INDUCTANCE: (@10kHz, 0. 1Vrms)
PIN1-2=700uH MAX (3-4 SHORT)
- 4. CAPACITANCE: (@1kHz, 0. 1Vrms)
PIN1-3=50pF MAX
- 5: TURN RATIO: (@3kHz, 0. 1Vrms)
PIN1-2:4-3=1 ±3%
- 6: HI-POT: (1250VAC, 1mA, 2SEC)
PRI-SEC-CORE
- 7. ROHS COMPLIANT

 苏州沃虎电子科技有限公司 Su Zhou Voohu Electronic Tech.Co.Ltd	TITLE: TRANSFORMER	SIZE A4	UNITS MM[INCH]	GENERAL TOLERANCES UNLESS SPECIFIED		APPROVED BY: Geoffrey.Song
	PART NO.: WHTT4101	SACLE 1:1	REV A0	x±0.35	x°±3.0°	CHECKED BY: Elvis.Song
	REMARK:	SHEET 1/1		.xx±0.25	.xx°±1.5°	DESIGND BY: Sunny.Xu
TEL: +86 400 1048 018	WEB: WWW.WOHU-TEK.COM			.xxx±0.10	.xxx°±1.0°	