



ELECTRICAL CHARACTERISTICS :

1. DCR PIN 1-3 = $75\Omega \pm 10\%$ PIN 4-6 = $75\Omega \pm 10\%$
2. INDUCTANCE (@250Hz, 0.5Vrms, PARALLEL) 1-3 = 2 H MIN.
3. IMPEDANCE (@1KHZ, 0dBm, 6-4 W/H 600Ω) 1-3 = $600\Omega \pm 15\%$
4. INSERTION LOSS = 1.5 dB MAX. (@1KHz, 0dBm, W/H 600Ω LOAD)
5. FREQ. RESP. (@300Hz TO 4KHz, REF. 1KHz) = ± 0.2 dB
6. RETURN LOSS: @300Hz = 20dB MIN. @1KHz = 20dB MIN.
@4KHz = 20dB MIN.
7. TURN RATIO : 1-3 : 6-4 = $1 \pm 1\%$
8. HI-POT = 1250 VAC, 1mA, 2SEC. (PRI.-SEC.)
9. RoHS COMPLIANT

VOOHU 苏州沃虎电子科技有限公司
Su Zhou Voohu Electronic Tech.Co.Ltd

TITLE: 600 : 400
TRANSFORMER

SIZE
A4

UNITS
MM[INCH]

GENERAL TOLERANCES
UNLESS SPECIFIED

APPROVED BY:

Geoffrey.Song

PART NO.:
WHTT4V150

SACLE
1:1

REV
A0

$x \pm 0.35$
 $.x \pm 0.30$

$x^\circ \pm 3.0^\circ$
 $.x^\circ \pm 2.0^\circ$

CHECKED BY:

Elvis.Song

TEL: +86 400 1048 018

WEB: WWW.WOHU-TEK.COM

REMARK:

SHEET
1/1



$.xx \pm 0.25$
 $.xxx \pm 0.10$

$.xx^\circ \pm 1.5^\circ$
 $.xxx^\circ \pm 1.0^\circ$

DESIGND BY:

Sunny.Xu