

ELECTRICAL CHARACTERISTICS:

1.DCR:

PIN1-3=140 OHM MAX

PIN6-4=170 OHM MAX

2.INDUCTANCE PARALLEL:1KHz,1V

PIN1-3=1.7H MIN

3.INSERTION LOSS:1KHz,0dB

PIN1-3(6-4 W/H 600 OHM)=2dB MAX

4.RETURN LOSS:(6-4W/H600 OHM)

350Hz=10dB MIN

1KHz=10dB MIN

3.5KHz=10dB MIN

5.TURN RATIO:1KHz,1V

PIN1-3:6-4=1±2%

6.HI-POT: 1000vAC 1mA 2SEC:P-S

7.ROHS COMPLIANT

**VOOHU** 苏州沃虎电子科技有限公司  
Su Zhou Voohu Electronic Tech.Co.Ltd

TITLE:  
DRAWING

PART NO.:  
WHTT40Q1

REMARK:


SIZE  
A4

SACLE  
1:1

SHEET  
1/1

UNITS  
MM[INCH]

REV  
A0



GENERAL TOLERANCES  
UNLESS SPECIFIED

$x \pm 0.35$	$x^\circ \pm 3.0^\circ$
$.x \pm 0.30$	$.x^\circ \pm 2.0^\circ$
$.xx \pm 0.25$	$.xx^\circ \pm 1.5^\circ$
$.xxx \pm 0.10$	$.xxx^\circ \pm 1.0^\circ$

APPROVED BY:  
Geoffrey.Song

CHECKED BY:  
Elvis.Song

DESIGND BY:  
Sunny.Xu

TEL: +86 400 1048 018

WEB: WWW.WOHU-TEK.COM